

SEMICONDUCTOR LASER

Patent Number: JP1256189
Publication date: 1989-10-12
Inventor(s): SAKATA AKIHIRO
Applicant(s): MATSUSHITA ELECTRIC IND CO LTD
Requested Patent: ☐ JP1256189
Application Number: JP19880084730 19880406
Priority Number(s):
IPC Classification: H01S3/18; G11B7/125
EC Classification:
Equivalents:

Abstract

PURPOSE: To stabilize the amount of projection light by inclining a projection window of laser beam and by controlling projection power of laser according to the light amount which is received at a PIN diode arranged at the side.

CONSTITUTION: A laser chip 3 is fixed to a post 2 on a base 1 and front projection light 10 is projected from an upper edge surface of the laser chip 3. A projection window 21 is arranged aslant to an optical axis and its angle depends on a thickness of the projection window 21 and an astigmatic difference of a laser. The beam reflected at the projection window 21 incidents to a PIN diode 6 which is fixed to a PIN diode post 22 at the side and the beam reflected at a surface of the PIN diode 6 returns to the laser chip 3, resulting in the reduction of noises. The amount of projection light from a laser can be stabilized in this way.

Data supplied from the **esp@cenet** database - I2



(19)

(11) Publication number:

0

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **63084730**(51) Intl. Cl.: **H01S 3/18 G11B 7/125**(22) Application date: **06.04.88**

<p>(30) Priority:</p> <p>(43) Date of application publication: 12.10.89</p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: MATSUSHITA ELECTRIC LTD</p> <p>(72) Inventor: SAKATA AKIHIRO</p> <p>(74) Representative:</p>
---	---

(54) SEMICONDUCTOR LASER

(57) Abstract:

PURPOSE: To stabilize the amount of projection light by inclining a projection window of laser beam and by controlling projection power of laser according to the light amount which is received at a PIN diode arranged at the side.

CONSTITUTION: A laser chip 3 is fixed to a post 2 on a base 1 and front projection light 10 is projected from an upper edge surface of the laser chip 3. A projection window 21 is arranged aslant to an optical axis and its angle depends on a thickness of the projection window 21 and an astigmatic difference of a laser. The beam reflected at the projection window 21 incidents to a PIN diode 6 which is fixed to a PIN diode post 22 at the side and the beam reflected at a surface of the PIN diode 6 returns to the laser chip 3, resulting in the reduction of noises. The amount of projection light from a laser can be

stabilized in this way.

COPYRIGHT: (C)1989,JPO&Japio

